



PG58 Vocal Microphone

A rugged microphone tuned to accentuate the clarity of lead and back-up vocals.

- **PG58-QTR** includes a 15ft (4.57m) XLR to 1/4" Cable, Microphone Clip, 5/8" to 3/8" Thread Adapter, and a Storage Bag.
- **PG58-XLR** includes a 15ft (4.57m) XLR to XLR Cable, Microphone Clip, 5/8" to 3/8" Thread Adapter, and Storage Bag.
- **PG58-LC** includes a Microphone Clip, 5/8" to 3/8" Thread Adapter and a Storage Bag.

- Tailored frequency response is smooth and extended. Tuned specifically for vocal applications.
- Cardioid polar pattern picks up the most sound from in front of the microphone and some sound from the sides. Less susceptible to feedback in high volume settings.
- Dynamic cartridge has a simple, rugged coil. Handles extreme volume levels without distortion.
- Cartridge includes a neodymium magnet for high output level.
- Internal shock mount for reduced handling noise.
- Durable metal construction.
- On/off switch for onstage control.
- Hardened steel mesh ball grille that resists wear and abuse.
- Integral "pop" filter reduces explosive breath sounds and wind noise.
- Includes 15ft (4.57m) cable, break-resistant mic clip and storage bag.
- Replacement cartridge: [RPM150](#).

Microphone Type


Dynamic (moving coil)

Polar Pattern

Cardioid (unidirectional)

Frequency Response

60 to 15,000 Hz



[view larger](#)

Polarity

Positive pressure on diaphragm produces positive voltage on pin 2 relative to pin 3 of microphone output connector

Output Impedance (at 1000 Hz)

300 ohms

Sensitivity (at 1000 Hz)

-53 dBV/Pa, (2.2 mV), 1 Pascal=94 dB SPL

Electromagnetic Hum Sensitivity

26 dB equivalent SPL in a 1 millioersted field (60 Hz)

Switch

Built-in On/Off switch

Connector

Three-pin professional audio connector (male XLR type)

Case

Die cast metal handle, black matte finish; hardened silver colored, spherical steel mesh grille

Environmental Conditions

This microphone operates over a temperature range of -29 to 57 degrees Celsius (-20 to 135 degrees Fahrenheit), and at a relative humidity of 0 to 95%.

Weight

Net: 321 g (11.3 oz)
Packaged: 908 g (2 lb)



A25D Microphone Clip

Securely mounts the SM58, SM57, SM87A, Beta 87A and all other microphones with 3/4-inch and larger handles to a standard microphone stand.

Available Online



A58WS Microphone Windscreen

Reduces unwanted breath and wind noise. For use with all larger Shure "ball-type" microphones including the SM58, Beta58A, SM48, and the 565SD. Available in 6 colors; black, blue, gray, green, red, and yellow.

Available Online



RPM150, RPM152 and RPM154 Cartridges for PG Mics

Replacement Microphone Cartridges for Performance Gear models PG52, PG56, PG57 and PG58.

User Guide Chinese	1956 KB PDF
User Guide English	1106 KB PDF
User Guide French	1135 KB PDF
User Guide German	1112 KB PDF
User Guide Italian	1105 KB PDF
User Guide Japanese	1860 KB PDF
User Guide Portuguese	1103 KB PDF
User Guide Spanish	1112 KB PDF